

# ProJet® MJP 2500 IC



## ProJet MJP 2500 IC

<b>Printing Mode</b>	HD - High Definition
<b>Net Build Volume (xyz)*</b>	11.6 x 8.3 x 5.6 in (294 x 211 x 144 mm)
<b>Resolution (xyz)</b>	600 x 600 x 600 DPI; 42 µm layers
<b>Accuracy (typical)**</b>	±0.004 in/in (±0.1016 mm/25.4 mm) of part dimension across printer population ±0.002 in/in (±0.0508 mm/25.4 mm) of part dimension typical for any single printer
<b>Volumetric Print Speed</b>	1 Lane 12.5 in <sup>3</sup> /hour (205 cm <sup>3</sup> /hour) 2 Lanes 12.1 in <sup>3</sup> /hour (199 cm <sup>3</sup> /hour) 3 Lanes 11.6 in <sup>3</sup> /hour (189 cm <sup>3</sup> /hour)
<b>Build Material</b>	Visijet® M2 ICast
<b>Support Material</b>	Visijet® IC SUW
<b>Material Packaging</b>	In clean 2.87 lbs (1.3 kg) bottles (printer holds up to 2 with auto-switching)
Build Material	
Support Material	In clean 2.87 lbs (1.3 kg) bottles (printer holds up to 2 with auto-switching)
<b>Electrical</b>	100-127 VAC, 50/60 Hz, single-phase, 15A 200-240 VAC, 50 Hz, single-phase, 10A Single C14 receptacle
<b>Dimensions (WxDxH)</b>	
3D Printer Crated	55 x 36.5 x 51.7 in (1397 x 927 x 1314 mm)
3D Printer Uncrated	44.1 x 29.1 x 42.1 in (1120 x 740 x 1070 mm)
<b>Weight</b>	
3D Printer Crated	716 lb (325 kg)
3D Printer Uncrated	465 lb (211 kg)
<b>3D Sprint® Software</b>	Easy build job set-up, submission and job queue management; Automatic part placement and build optimization tools; Part stacking and nesting capability; Extensive part editing tools; Automatic support generation; Job statistics reporting tools
<b>E-mail Notice Capability</b>	Yes
<b>Internal Hard Drive Capacity</b>	500 Gb minimum
<b>Connectivity</b>	Network ready with 10/100/1000 base ethernet interface USB port
<b>Client Operating System</b>	Windows® 7, Windows 8 or Windows 8.1 (Service Pack)
<b>Input Data File Formats Supported</b>	STL, CTL, OBJ, PLY, ZPR, ZBD, AMF, WRL, 3DS, FBX, IGES, IGS, STEP, STP, MJPDDD
<b>Operating Temperature Range</b>	Optimal 64-75 °F (18-24 °C), not to exceed 82 °F (28 °C)
<b>Operating Humidity</b>	30-70 % relative humidity
<b>Noise</b>	< 65 dBA estimated (at medium fan setting)
<b>Certifications</b>	CE, UL, EAC, KCC and FCC

\* Maximum part size is dependent on geometry, among other factors.

\*\* Across printer variation can be reduced to equal single printer variation via user calibration.

Accuracy may vary depending on build parameters, part geometry and size, part orientation, and post-processing.




# Visijet® M2 ICast

High performance RealWax™ material for direct metal casting



Properties	Condition	Visijet M2 ICast	Visijet M2 IC SUW
Composition		100% Wax	Wax Support Material
Color		Green	White
Bottle Quantity		1.3 kg	1.3 kg
Density @ 80 °C (liquid)	ASTM D3505	0.80 g/cm <sup>3</sup>	0.87 g/cm <sup>3</sup>
Melting Point		61-66 °C	55-65 °C
Softening Point		40-48 °C	N/A
Volumetric Shrinkage, from 40 °C to RT		2 %	N/A
Linear Shrinkage, from 40 °C to RT		0.70 %	N/A
Needle Penetration Hardness	ASTM D1321	12	N/A
Ash Content	ASTM 2584	< 0.05 %	N/A
Printer Compatibility		Projet MJP 2500 IC	Projet MJP 2500 IC
Description		High resolution, durable casting wax An unfilled paraffin based wax with added resins	Non-toxic wax support material with easy break-away structure and dissolvable hands-free removal



Print the Future

3DZ Franchising (Malta)  
3DZ Treviso (Castelfranco Veneto)  
3DZ Brescia (Rezzato)  
3DZ Piedmont (Casale Monferrato)  
3DZ Rome (Rome)  
3DZ Tuscany (Arezzo)  
3DZ Emilia (Reggio Emilia)  
3DZ Albania (Tirana)  
3DZ Ungheria (Budapest)  
3DZ Romania (Clujova)  
3DZ Barcelona (Spain)  
3DZ Andalusia (Spain)  
3DZ Madrid (Spain)  
3DZ Serbia (Belgrade)  
3DZ Dubai (Dubai)  
3DZ Lyon (Lyon)

(+356) 2713 915 2  
(+39) 0423 192307 0  
(+39) 030 638519 5  
(+39) 0142 23109 1  
(+39) 06 3973683 5  
(+39) 057 590854 2  
(+39) 0522 51695 0  
(+355) 688 08783 0  
(+36) 1794343 2  
(+40) 251 41976 4  
(+34) 938 441 720  
(+34) 953 88 80 89  
(+34) 912 24 30 84  
(+381) 11 265199 0  
(+941) 4251773 4  
(+33) 04 37693508

info@3dz.com.mt  
ty@3dz.it  
bs@3dz.it  
to@3dz.it  
roma@3dz.it  
info@tbnnet.it  
re@3dz.it  
tirana@3dz.al  
budapest@3dz.hu  
contact@cadworks.ro  
barcelona@3dz.es  
info@3dz.es  
madrid@3dz.es  
info@solfins.com  
info@3dz.com.mt  
info@3dz.fr